

On page, at line 4, insert the following immediately following line 3:

## **BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention should be more fully understood when the specification herein is taken in conjunction with the drawings appended hereto wherein:

Figure 1 shows a top view, Figure 2 shows a side view and Figure 3 shows an end view of one embodiment of a present invention fastener holding device;

Figure 4 shows a partial top view of a blown up version of another present invention fastener holding device;

Figure 5 shows a partial, cut top view of another present invention fastener holding device, shown holding a screw;

Figures 6, 7, 8 and 9 show another alternative embodiment present invention fastener holding device, in top, side, and cut end views;

Figure 10 shows an accessory for present invention fastener holding devices, namely, an electrical lug retainer;

Figures 11, 12 and 13 show a top, side and end view, respectively, of another present invention fastener holding device; and,

Figure 14 shows a partial top view and Figure 15 shows that view with a screw being held, of another present invention fastener holding device.

On page 8, beginning at line 7, delete the entire paragraph and insert the following in its place:

In preferred embodiments, the present invention device inside opposing surfaces of each pair of gripping fingers are symmetric relative to one another. In other embodiments, they are asymmetric. In these asymmetric embodiments the gripping fingers are irregular, offset and/or reversed relative to one another. For example, the inside opposing surfaces of a pair of gripping fingers may include one finger with a recess area and one opposing finger with a protrusion area. Preferably, the recess area is larger than the opposing protrusion area to enhance retention of a fastener.